



Outdoor
Patio Furnishings

Assembly Instructions

For Avonlea Garden Bench

Tools Needed: hammer, 7/16" wrench, #2 square bit screw driver or power driver, No drilling is required. All the necessary holes are predrilled.



Parts

12 - 2 1/2" Screws
 8 - 2" Screws
 10 - 1 3/4" Screws

Back assembly
 2 Seat supports
 2 Seat skirts
 2 leg assemblies
 Seat assembly

Lay the parts on a protected surface such as cardboard or blankets to assemble them.

Step 3 – Fasten seat assembly

2" screws, seat assembly

Insert the seat assembly resting the front and back on the seat skirts. Fasten with eight 2" screws underneath the seat.

Step 1 – Fasten left leg assembly

2 1/2" Screws, left leg assembly, back assembly, seat skirts

Place the left arm assembly on a clean, flat work surface. Insert the two seat skirts and the seat back into the left arm assembly. Position the skirts so the tag shows on the backside of the bench. The slats in the back assembly are not centered in the rails. Turn the back assembly so the slats are positioned toward the back. Use a rubber mallet to tap the joints tight. Fasten with six 2 1/2" screws using the pilot holes in the left arm assembly.

Step 4 – Fasten seat supports

1 3/4" Screws, seat supports

Place the seat supports underneath the seat against the outside. Be sure the support is tight against the seat slats. Screw in place with 1 3/4" screws using the pilot holes.

Step 2 – Fasten right leg assembly

2 1/2" Screws, right leg assembly

Place the right leg assembly on top. Align holes and use a rubber mallet to tap the joints tight. Fasten with six 2 1/2" screws using the pilot holes in the right leg assembly.

Congratulations!
Your Avonlea Garden
Bench is ready to enjoy!



*When installing screws, tighten till the head goes slightly below the surface.