



Outdoor  
Patio Furnishings

# Assembly Instructions

For SeaAira Child's Chair

**Tools Needed:** hammer, 7/16" wrench, #2 square bit screw driver or power driver, No drilling is required. All the necessary holes are predrilled. Bolts fit snugly in the holes. You may need to use a hammer to drive the bolts through the holes.



## Parts

4 - 2" Screws  
4 - 2 1/2" Screws  
4 - 2" Carriage bolts with nuts

Back assembly  
Seat assembly  
2 leg assemblies

Lay the parts on a protected surface such as cardboard or blankets to assemble them.

## Step 2 — Attach leg assemblies to seat assembly

4 - 2 1/2" Screws, 2 leg assembly

Fasten the legs using the carriage head bolts. Tap the bolt heads with a hammer to set them firmly against the leg. Tighten nuts securely. Use 2 1/2" screws to fasten the back of the arm to the seat back.

Repeat the step above with the second leg assembly.

## Step 1 — Attach back assembly

4 - 2" Screws, back assembly, seat assembly

Place the back assembly on a clean, flat work surface. Attach the back assembly with four 2" screws.

Congratulations!  
Your SeaAira Child's  
Chair is ready to enjoy!



\*When installing screws, tighten till the head goes slightly below the surface.